

Muli-Nova DDP

Product information for the product group

ACO Product benefits

- Tested in accordance with DIN EN 12050-1
- Freely selectable inlets
- Delivery heads of up to 30m possible
- 2 container sizes selectable (430/ 440l)
- Easy to maintain backflow preventer (patented)




- Scope
 - Multi-dwelling units
 - Office buildings
 - Industrial buildings
 - Behind separators up to NS20 - in connection with air bubble injection
- Polyethylene tank
 - Bottom outlet/ connection manual membrane pump R 1 1/2'
 - Inspection opening for easy maintenance, diameter: 250 mm
 - Fastening set for buoyancy-proof anchorage
 - DDP 1.x:
 - Horizontal inlet sockets 1x DN100, 1x DN150
 - Vertical inlet sockets: 1x DN100, 3x DN150, 1x DN200, 1x DN100 (vent pipes)
 - DDP 2.x:
 - Horizontal inlet sockets 3x DN150
 - Vertical inlet sockets: 1x DN100, 2x DN150, 1x DN200, 1x DN100 (vent pipes)
 - In addition, freely selectable sockets per hole saw + seal
- Discharge line connection
 - Patented flap backflow preventer with lifting screw
 - Drain valve for easier draining
 - Special mounting adapter DN 80 for elastic connection of the discharge line with 108 - 114.3 mm outer pipe diameter (optional 88 - 93 mm)
 - Connecting flange for stop valve DN 80
- 2 pumps
 - 3-phase motor: 400 V, 50 Hz
 - Degree of protection IP 68
 - Blockage-free free flow impeller
 - 10 m connecting cable
- Level switching
 - Pneumatic level switching with 10 m control line
 - Optional: Pressure transducer
 - Optional: Air bubble injection (accessories) for measurement with pilot tube
- Tested in accordance with DIN EN 12050-1
- Approved delivery temperature up to 40 °C (short-term up to max. 65 °C)
- Control is not included in the scope of supply and must be ordered separately (see accessories)



Item Technical Data 3016808

Type	Motor power		Power consumption [A]	Key data			Usable volume		Total volume [l]	Weight [kg]
	P1	P2		Voltage [V]	Rev count [r/min]	Inlet height Z1 [l]	Inlet height Z2 [l]	Top inlet [l]		
	[kW]	[kW]								
Muli-Nova DDP 1.1	1.7	1.5	3.7	400	1450	100	275	345	430	105


Dimensions



- 1) Spezialbefestigungsstück für den elastischen Anschluss der Druckleitung DN100/
Special fastening piece for elastic connection of the DN100 pressure line





Schaltkasten (steckerfertig)/
Switch box (plug-in ready)
Kabel (1,5 m lang) mit CEE-Stecker 32A/
Cable (1.5m long) with CEE-connector 32A




Performance parameters
















Type	Deliv- ery head [m]	Delivery flow Q with overall delivery head H					Media temperature	
		2 m [l/s]	4 m [l/s]	6 m [l/s]	8 m [l/s]	10 m [l/s]	Normal [°C]	Maximum [°C]
Muli-No- va DDP 1.1	2 – 10	14.4	12.1	9.2	5.3	0.4	40	60






Accessories



Description	Used with	Weight	PU	Item number
		[kg]	[piece]	
<ul style="list-style-type: none"> ■ For pumps up to 5,5 kW ■ Plug and use with 1.5 m mains cable ■ Operating voltage: 400 V ■ Frequency: 50/60 Hz ■ Control voltage: 230 V/AC ■ Current consumption when idling: max 10 VA ■ Temperature range: -20 to +60 ° C ■ IP 54 protection 		5.4		
	<p>Switching device, ACO Multi Control Duo Professional without Dynamic pressure bellWith Modbus RTU functionality for connection to the building management system; CEE 16 plug with phase-changing switch;</p> <p><input type="checkbox"/> Convertible to CEE 32 with item no. 0150.79.75 (5G4 with CEE 32 plug) ; 20 m pneumatic control cable 8 x 6 mm</p>	<p>Muli-Nova DDP; <input type="checkbox"/> Muli-Nova x.1 / x.2</p>		3014981
	<p>Switching device, ACO Multi Control Duo Professional without Dynamic pressure bellWith Modbus RTU functionality for connection to the building management system; CEE 32 plug with phase-changing switch; 20 m pneumatic control cable 8 x 6 mm</p>	<p>Muli-Nova DDP; <input type="checkbox"/> Muli-Nova x.3</p>		3017236
	<p>Switching device, ACO Multi Control Duo without Dynamic pressure bellCEE 16 plug with phase-changing switch;</p> <p><input type="checkbox"/> Convertible to CEE 32 with item no. 0150.79.75 (5G4 with CEE 32 plug) ; Without control line</p>	<p>Muli-Max; <input type="checkbox"/> Duo ; Powerlift-P; Muli-Flex; Muli-Nova DDP; <input type="checkbox"/> Muli-Nova x.1 / x.2</p>		0178.63.94
	<p>Switching device, ACO Multi Control Duo without Dynamic pressure bellCEE 32 plug with phase-changing switch; Without control line</p>	<p>Muli-Nova DDP; <input type="checkbox"/> Muli-Nova x.3</p>		3017237

Description	Used with	Weight	PU	Item number
		[kg]	[piece]	
 <p>Message system with GSM module</p> <ul style="list-style-type: none"> ■ Parameter via app (Android & iOS) ■ Mains-independent alarm via 12V lead-gel battery ■ Optical and acoustic alarm message ■ Freely configurable inputs <ul style="list-style-type: none"> □ 6 digital inputs with LED status display □ 1 analogue ■ 1 alarm output 12 V ■ Alarm forwarding via SMS to mobile phones ■ For mounting outside the hazardous area ■ Housing: 192 x 150(with cable gland) x 100 mm (WxHxD) ■ Protective doctor: IP54 ■ Operating voltage: 230 V/AC 50/60 Hz 	<ul style="list-style-type: none"> ■ All grease separators ■ Grease layer thickness measuring device ■ Pre-tank plants ■ Technical processing systems ■ Quatrix-K backflow preventer type 3F ■ Sinkamat-K (underfloor) duo ■ Muli lifting units ■ Pumping stations ■ Installation sets 	2.0	1	0150.80.14
 <p>Connection cable antenna GSM</p> <ul style="list-style-type: none"> ■ Length incl. connections: approx. 15 m ■ Cable type: RG58 ■ Connections: 1 x SMA plug (SMA/M) and 1 x SMA socket (SMA/F) ■ Only one extension cable may be used per GSM module ■ Usable in temperature range: -20°C to 85°C 	■ GSM - Modul			0150.83.86
 <p>Signalling unit</p> <ul style="list-style-type: none"> ■ Self-charging ■ With floating contact ■ Visual and acoustic ■ Without contact transmitter ■ For mounting outside the potentially explosive atmosphere ■ Dimensions: 175 x 125 x 75 mm W x H x D ■ Protection type: IP65 ■ Operating voltage: 230 V/AC 50/60 Hz ■ Ready to plug in with cable: 2 m 				
	Faecal matter backflow automatic stop Quatrix-K type 3F; All Muli wastewater lifting plants; Upstream tank plant mono/duo; Muli-Max; Sinkamat -K/-KD; Sinkamat-Z; Sinkamat-Z (underfloor); <input type="checkbox"/> Duo ; LipuLift-P	1.4	1	0150.26.73

	Description	Used with	Weight [kg]	PU [piece]	Item number
	Connection and flood module set <ul style="list-style-type: none"> ■ To report a leak caused for example by a pipe bursting ■ For electrically conducting liquids ■ With volt free contact ■ Visible and audible alarms (approx. 80 dB) ■ Dimensions (width x height x depth): 160 x 120 x 75 mm ■ Protection level: IP 65 ■ Operating voltage: 230 V/AC 50/60 Hz ■ Plug and use: 1.4 m ■ Overflow indicator with 10 m cable 	<ul style="list-style-type: none"> ■ Triplex-K backflow stops <ul style="list-style-type: none"> □ DN 100 – DN 150 ■ Quatrix-K backflow stops ■ All wastewater lifting plants ■ All separators 	1.1	1	0150.78.97
	Signal horn <ul style="list-style-type: none"> ■ Operating voltage: 12V DC ■ Power consumption: 30 mA ■ 62 x 62 x 85 mm (LxWxD) ■ Degree of protection: IP66 ■ Noise level: 95 dB(A) 	<ul style="list-style-type: none"> ■ Signalling unit ■ Signalling unit with GSM module 	0.2		0150.58.14
	Signal horn <ul style="list-style-type: none"> ■ 230V AC ■ Power consumption: 30mA ■ Ø62x85 mm (L/B x T) ■ Protection: IP66 ■ 95 dB(A) 	<ul style="list-style-type: none"> ■ Signalling unit with voltage-free fault reporting ■ LipuSmart-P ■ Multi-Max with signalling unit ■ LipuLift-P 	0.3	1	0178.61.94
					
	230V; Power consumption: 70 mA	Signalling unit with voltage-free fault reporting; LipuSmart-P; Multi-Max with signalling unit; LipuLift-P	0.5	1	0178.62.08
					0150.76.25
	Air bubble injection <ul style="list-style-type: none"> ■ To increase operational safety (where floating surfaces are generated e.g. grease separator) ■ For pneumatic level switching ■ Mini compressor <ul style="list-style-type: none"> □ Connection: 230 V □ Plug and use ■ With T-screw-in connection ■ With backflow valve 				
		Multi-Max; Powerlift-P; Multi-Flex	0.6		0150.25.45
	Pressure pick-up <ul style="list-style-type: none"> ■ 4–20 mA ■ For secure switching cable lengths > 12 m ■ 0–200 mbar 				

Description	Used with	Weight	PU	Item number
		[kg]	[piece]	
With cable for installation: 20 m	Control ACO Multi-Control Mono/Duo; LipuLift-P/LipuLift-PF; Multi-Flex	2.0		0178.63.88
Cable for installation: 40 m	Control ACO Multi-Control Mono/Duo; LipuLift-P/LipuLift-PF; Multi-Flex	3.4		0178.63.87
 <p>Float switch</p> <ul style="list-style-type: none"> ■ Housing: PRE-ELEC PP ■ Degree of protection: IP68 ■ Switch voltage: 4-40 V ■ Switch current: 1-100 mA ■ Connection cable: 10m ■ Switch inclination: 10° ■ Protection class: II 1G Ex ia IIC T6 Ga 	<ul style="list-style-type: none"> ■ For faecal and non-faecal wastewater ■ MultiControl controls as float switches ■ MultiControl controls as additional High alarm float 			0159.12.45
 <p>Safety barrier</p> <ul style="list-style-type: none"> ■ To separate Ex-risk and secure areas ■ Incl. housing 	<ul style="list-style-type: none"> ■ Pressure pick-off ■ Float switch with ATEX-certificate 			
		0.5		0178.63.89
 <p>Sealing ring</p> <ul style="list-style-type: none"> ■ As additional component for pressure line DN 80 ■ Clamping range: 88 - 93 mm 	<ul style="list-style-type: none"> ■ LipuSmart-P ■ Powerlift installation kit DN 100 ■ Fäkablock II ■ All Muli wastewater lifting plants 	0.3	1	0150.83.71
 <p>Stop valve DN 80</p> <ul style="list-style-type: none"> ■ Made of cast iron ■ 8 screws and nuts ■ 1 DN 80 seal ■ Length: 180 mm 	<ul style="list-style-type: none"> ■ LipuSmart-P ■ Multi-Star MDP1/MWP1 ■ Multi-Star DDP 1/2 	19.4	1	0154.51.93
 <p>Inlet valve DN 100</p> <ul style="list-style-type: none"> ■ Made out of PVC ■ Spigot Ø110 on both sides for sleeveless pipe systems made of cast iron or plastic ■ Total dimensions: 176 x 360 mm (L x H) 	<ul style="list-style-type: none"> ■ Grease separator made of polyethylene ■ Starch separator made of polyethylene ■ Upstream tank systems type 2 and 4 ■ LipuMobil – type 0.5 	5.9		0175.31.87
 <p>Inlet valve DN 100</p> <ul style="list-style-type: none"> ■ Made of PVC ■ 110 mm push socket on both sides with rim sealing ring ■ Overall dimensions: 176 x 330 mm (L x H) 	<ul style="list-style-type: none"> ■ Wastewater lifting plant ■ Polyethylene grease separator ■ Polyethylene starch separator ■ Upstream tank plant <ul style="list-style-type: none"> □ Typ 2 and 4 ■ LipuMobil-P – Type 0.5 	3.1	1	0175.13.84
 <p>Inlet valve DN 150</p> <ul style="list-style-type: none"> ■ Made of PVC ■ 160 mm push socket on both sides with rim sealing ring ■ Overall dimensions: 226 x 510 mm (L x H) 	<ul style="list-style-type: none"> ■ Wastewater lifting plant ■ Polyethylene grease separator ■ Polyethylene starch separator ■ Upstream tank plant <ul style="list-style-type: none"> □ Type 7 – Type 10 	7.0	1	0175.13.85

	Description	Used with	Weight [kg]	PU [piece]	Item number
	<p>Inlet valve DN 150</p> <ul style="list-style-type: none"> ■ Made out of PVC ■ Spigot Ø110 on both sides for sleeveless pipe systems made of cast iron or plastic ■ Total dimensions: 226 x 420 mm (L x H) 	<ul style="list-style-type: none"> ■ Grease separator made of polyethylene ■ Starch separator made of polyethylene ■ Upstream tank systems type 7 to 10 	10.2		0175.31.88
	<p>Inlet valve DN 200</p> <ul style="list-style-type: none"> ■ Made out of PVC ■ Push socket 200 mm with lip sealing ring on both sides ■ Total dimensions: 264 x 637 mm (L x H) 	<ul style="list-style-type: none"> ■ Wastewater lifting plant <ul style="list-style-type: none"> <input type="checkbox"/> Multi-Star DDP 1/2 ■ Grease separator made of polyethylene <ul style="list-style-type: none"> <input type="checkbox"/> From NS 15 	8.4	1	0170.20.83
		<ul style="list-style-type: none"> ■ Abwasserhebeanlage <ul style="list-style-type: none"> <input type="checkbox"/> Multi-Nova DDP 			
	<p>Inlet seal DN 50ACO inlet seal DN 50; For insertion of an additional inlet; For pipe with OD 50 mm; Drilling diameter 59 mm</p>				3013641
	<p>Inlet seal DN 70ACO inlet seal DN 70; For insertion of an additional inlet; For pipe with OD 75mm; Drilling diameter 86 mm</p>				3014479
	<p>Inlet seal DN 100ACO inlet seal DN 100; For insertion of an additional inlet; For pipe with OD 110mm; Drilling diameter 125 mm</p>				3014478
	<p>Inlet seal DN 150ACO inlet seal DN 150; For insertion of an additional inlet; For pipe with OD 160mm; Drilling diameter 175 mm</p>				3014477
	<p>Inlet seal DN 200ACO inlet seal DN 200; For insertion of an additional inlet; For pipe with OD 200mm; Drilling diameter 215 mm</p>				3014476
	<p>Inlet seal DN 250ACO inlet seal DN 250; For insertion of an additional inlet;; For pipe with OD 250mm;; Drill diameter 265 mm</p>				3014475
	<p>Hand membrane pump 1 1/2"</p> <ul style="list-style-type: none"> ■ For fixing to wall ■ Incl. hose <ul style="list-style-type: none"> <input type="checkbox"/> Clear width: 48 x 80 mm ■ Incl. hose clamp <ul style="list-style-type: none"> <input type="checkbox"/> Clear width: 50 x 70 mm <input type="checkbox"/> Width: 12 mm <input type="checkbox"/> 2 pcses required 	<ul style="list-style-type: none"> ■ Wastewater lifting plant 	14.4	1	0175.23.73
	<p>Three way valve 1 1/2"</p> <ul style="list-style-type: none"> ■ For hand membrane pump 	<ul style="list-style-type: none"> ■ Wastewater lifting plant 	3.3	1	0159.10.14

Description	Used with	Weight	PU	Item number
		[kg]	[piece]	
 <p>Stop valve 1 1/2" ■ For hand membrane pump</p>	<p>■ Wastewater lifting plant</p>	1.0	1	0159.10.12
 <p>siphon</p>		0.7		0174.02.29
		1.3		0174.02.30

You can find further accessories under → <https://www.buildingdrainage.aco/search/?q=3016808>